



The World Leader
In Data Elimination

Degaussers Comparison Chart



TS-4XT IRONCLAD Degausser with Erasure Verification System



TS-4XT 40,000 Gauss Degausser



TS-1XT IRONCLAD Degausser with Erasure Verification System



TS-1XT NSA/EPL Listed Degausser



HD-3XTL IRONCLAD Degausser with Erasure Verification System



HD-3XTL High-Volume Degausser



HD-2XT IRONCLAD Degausser with Erasure Verification System



HD-2XT High-Speed Degausser

Specifications				
Certifications/Listings	ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC	NSA/CSS • ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC	UL • ETL • IEC • CSA • CE • RCM • TAA • FCC	UL • ETL • IEC • CSA • CE • RCM • TAA • FCC
Verification Options	SCAN-1X standard • IRONCLAD optional	SCAN-1X standard • IRONCLAD optional	SCAN-1X standard • IRONCLAD optional	IRONCLAD or SCAN-1X optional
Magnetic Field	4 tesla (40,000 gauss) NOM	2 tesla (20,000 gauss) NOM	1 tesla (10,000 gauss) NOM	1 tesla (10,000 gauss) NOM
Drawer/Slot Capacity (HxWxD)	1x 4 x 5.8 (in.) 25.4 x 101.6 x 147.3 (mm)	1.25 x 4.3 x 5.9 (in.) 31.8 x 108 x 148.6 (mm)	1.7 x 4.5 x 5.9 (in.) 43.2 x 114.3 x 148.6 (mm)	1.25 x 4.3 x 5.9 (in.) 31.8 x 108 x 148.6 (mm)
Media Types	Hard drives: Laptop, standard, or network up to 1 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others	Hard drives: Laptop, standard, or network up to 1.25 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others	Hard drives: Hard drives up to 1.7 in. in height including full height, standard and laptop drives Tape media: All LTO, all DLT, 3490, 9940, 3592, AIT, and others	Hard drives: Laptop, standard, network up to 1.25 in. in height Tape media: All LTO, all DLT, AIT, 2590 series, 8mm, and others
Continuous Duty	✓	✓	✓	✓
Degausser Throughput (hard drives per hour)	Up to 480 (1.8 in.) Up to 360 (2.5 in.) Up to 80 (3.5 in.)	Up to 1,300 (1.8 in.) Up to 875 (2.5 in.) Up to 150 (3.5 in.)	Up to 4,500 (1.8 in.) Up to 4,500 (2.5 in.) Up to 450 (3.5 in.)	Up to 1920 (1.8 in.) Up to 960 (2.5 in.) Up to 240 (3.5 in.)
Throughput with IRONCLAD (hard drives per hour)	Up to 80	Up to 120	Up to 240	Up to 180
Charge Time	~30 seconds	15 seconds	3 seconds	8 seconds
Power	TS-4XT: 90-250VAC ±5%, 50/60 Hz IRONCLAD: 90~240V 47-440 Hz	TS-1XT: 90-250VAC ±5%, 50/60 Hz IRONCLAD: 90~240V 47-440 Hz	HD-3XTL: 90~250VAC ±5%, 50/60 Hz IRONCLAD: 90~240V 47-440 Hz	HD-2XT: 90-250VAC ±5%, 50/60 Hz IRONCLAD: 90~240V 47-440 Hz
Weight	TS-4XT: 130 lbs. (59 kg.) Touchscreen: 4 lbs. (1.7 kg)	TS-1XT: 105 lbs. (47.7 kg.) Touchscreen: 4 lbs. (1.7 kg)	HD-3XTL: 59 lbs. (27 kg.) Touchscreen: 4 lbs. (1.7 kg)	HD-2XT: 34 lbs. (15.4 kg.) Touchscreen: 4 lbs. (1.7 kg)
Size (HxWxD)	TS-4XT IRONCLAD: 19.3 x 9.8 x 29.1(in.) 490 x 247.7 x 740.2 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)	TS-1XT IRONCLAD: 19.3 x 9.8 x 29.1(in.) 490 x 247.7 x 740.2 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)	HD-3XTL IRONCLAD: 18.9 x 25.1 x 13 (in.) 480 x 637.5 x 328.9 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)	HD-2XT IRONCLAD: 10.2 x 17.75 x 18.2 (in.) 260 x 451 x 463 (mm) Touchscreen: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64 (mm)
Power Consumption	Under standby: 108W While charging: 1272W (avg) At the time of erase: 120W IRONCLAD: 15W	Under standby: 108W While charging: 1272W (avg) At the time of erase: 120W IRONCLAD: 15W	Under standby: 36W While charging: 300W (avg) At the time of erase: 36W IRONCLAD: 25W	Under standby: 17W While charging: 145W (avg) At the time of erase: 17W IRONCLAD: 15W
Capacitive Discharge	✓	✓	✓	✓
Warranty	TS-4XT: One-year manufacturer's limited warranty standard, optional three year limited warranty TS-4XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard	TS-1XT: One-year manufacturer's limited warranty standard, optional three year limited warranty TS-1XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard	HD-3XTL: One-year manufacturer's limited warranty standard, optional three year limited warranty HD-3XTLA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard	HD-2XT: One-year manufacturer's limited warranty standard, optional three year limited warranty HD-2XTA/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard



The World Leader
In Data Elimination

Destroyers Comparison Chart



PD-5 IRONCLAD
Hard Drive Destroyer with
Destruction Verification



PD-5
Hard Drive Destroyer



SSD-1 Solid-State Destroyer
(for use with the PD-5)



FLASHPRO IRONCLAD
Solid-State Shredder with
Destruction Verification



FLASHPRO
Solid-State Shredder

Specifications	PD-5 IRONCLAD Hard Drive Destroyer with Destruction Verification	PD-5 Hard Drive Destroyer	SSD-1 Solid-State Destroyer (for use with the PD-5)	FLASHPRO IRONCLAD Solid-State Shredder with Destruction Verification	FLASHPRO Solid-State Shredder
Certifications/Listings	NSA/CSS • ETL • UL • IEC • CSA • CE • KC • RCM • TAA • FCC		TAA • Patented	CE • Meets E-3 Security Requirements • TAA	
Verification Options	IRONCLAD or SCAN-1X options		IRONCLAD and SCAN-1X capable	IRONCLAD optional	
Destruction Chamber Capacity (HxWxD)	2.26 x 4.9 x 6.8 (in.) 57.4 x 123.7 x 172.2 (mm)		0.5 x 3 x 6 (in.) 13.2 x 73.7 x 152.4 (mm)	6.5 in. (165 mm)	
Media Types	Laptop, standard, or network hard drives up to 2.25 in. in height ¹		SSD, flash drives, USB thumb drives, mobile phones ² , SSHD controller boards ¹	Mobile phones ² , mini-tablets (up to 6.5 in. or 165 mm in width) ² , solid-state drives (SSD) ¹ , USB thumb drives, and optical media	
Throughput (hard drives per hour)	Up to 1,800 (2.5 in.) Up to 360 (3.5 in.)		180-720 pieces per hour (depending on size of media)	100 Mobile phones** 500 SSD drives* 500 USB thumb drives 500 CDs\DVDs	
Throughput With IRONCLAD (hard drives per hour)	Up to 180 (hard drives per hour)		.	Up to 180 pieces of media	
Cycle Time	20 seconds		20 seconds	Depends on media size	
Crush Force	10+ tons		90 spikes	.	
Shred Size	.		.	0.16 x 0.6 in. (4 x 15 mm)	
Weight	79 lbs. (35.9 kg.) • Touchscreen: 4lbs. (17 kg.)		8.3 lbs. (3.8 kg.)	256 lb (116 kg)	
Size (HxWxD)	14.9 x 7.5 x 18.6 (in.) 377.7 x 190.8 x 473.5 (mm)		2.8 x 4.8 x 6.8 (in.) 71.1 x 121.9 x 173.4 (mm)	39 x 22.8 x 24 (in.) 990.6 x 579.1 x 609.6 (mm)	
Power	PD-5: 100-240VAC ±5%, 50/60 Hz IRONCLAD: 90~240V 47-440 Hz		.	120 V/60 Hz, 230 V/50 Hz, 240 V/50 Hz* (Plugs into 20A receptacle) IRONCLAD: 90~240V 47-440 Hz	
Power Consumption	During standby: 90W During crush: 1200W (max)		.	During standby: 8.4W Running no load: 960W (max) Running with load: 1450W avg. / 2400W max.	
Accessories Included	.		5 SSD-MT media transport sleeves for destroying solid-state media	Catch basket Plastic bag Oil bottle	
Warranty	PD-5: One-year manufacturer's limited warranty standard, optional three year limited warranty PD-5A/E • IRONCLAD: One-year manufacturer's limited warranty standard Scanner: Ninety-day manufacturer's limited warranty standard		SSD-1 • SSD-1A/E: Ninety-day manufacturer's limited warranty standard	FLASHPRO • FLASHPRO-A/E: One-year manufacturer's limited warranty standard	

¹ Enterprise SSDs must have rack mounts and casings removed prior to destruction

² All items must have the battery removed prior to destruction



The World Leader
In Data Elimination

Verification Comparison Chart



IC-TSXT
Erasure Verification System



IC-HD3XTL
Erasure Verification System



IC-HD2X
Erasure Verification System



IC-SSC25SSD
Erasure Verification System



IC-PD5
Destruction Verification System



IC-FLASHPRO
Destruction Verification System



IC-UNIVERSAL
Destruction Verification System



SCAN-1X
Media Destruction Report Package

Specifications

Certifications/ Listings	UL • ETL • IEC • CSA • CE • FCC • TAA	UL • ETL • IEC • CSA • CE • FCC • TAA	UL • ETL • IEC • CSA • CE • FCC • TAA	UL • ETL • IEC • CSA • CE • FCC • TAA	UL • ETL • IEC • CSA • CE • FCC • TAA	CE • Security Level DIN 66399 O-3 / T-4 / E-3 • TAA	UL • ETL • IEC • CSA • CE • FCC • TAA	N/A	
To be used with	TS-4XT 40,000 Gauss degausser TS-1XT NSA-listed degausser	HD-3XTL high-volume degausser	HD-2XT high-speed degausser	SPACESAVER Compliance Package	PD-5 physical destroyer	FLASHPRO	UNIVERSAL application	TS-1XT • TS-1XT • HD-3XTL • HD-2XT • HD-2XTSS • PD-5	
Includes	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head, • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • IRONCLAD software to generate Certificate of Erasure and Destruction • Touch screen control head • Image capture device • Barcode scanner 	<ul style="list-style-type: none"> • Media destruction report software • Barcode scanner 	
Hardware Needed	•	•	•	•	•	•	•	Laptop, desktop computer, or tablet	
Storage Capacity	16GB	16GB	16GB	16GB	16GB	16GB	16GB	•	
Weight	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.2 lbs (.5 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 9.5 lbs (4.3 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)	Control Head: 4 lbs (1.7 kg) Camera Unit: 1.1 lbs (.5 kg)	1.6 lbs. (.73 kg)	
Size (HxWxD)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 7.7 x 7.8 x 5 (in.) 197 x 198 x 127 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 14.5 x 11.9 x 6.4 (in.) 369 x 303 x 163 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 9 x 5.5 x 5.8 (in.) 229 x 140 x 146 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 9 x 5.5 x 5.8 (in.) 229 x 140 x 146 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 8.2 x 5.7 x 5.6 (in.) 208 x 146 x 142 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 8.2 x 5.7 x 5.6 (in.) 208 x 146 x 142 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 8.2 x 5.7 x 5.6 (in.) 208 x 146 x 142 (mm)	Control Head: 6.6 x 9.6 x 2.5 (in.) 168 x 244 x 64(mm) Camera Unit: 8.2 x 5.7 x 5.6 (in.) 208 x 146 x 142 (mm)	8.7 X 6.5 X 3.4 (in.) 221 x 165 x 86.4 (mm)
Power Requirements	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	90-240VAC, 47-440 Hz	•	
Power Consumption	15W	25W	15W	15W	15W	15W	15W	•	
Warranty	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	IRONCLAD: One-year manufacturer's limited warranty standard. Scanner: Ninety-day manufacturer's limited warranty standard	Scanner: Ninety-day manufacturer's limited warranty standard	



The World Leader
In Data Elimination

Packages Comparison Chart



EDC
Enclosed Destruction Cart



RCC
Data Eliminator Cart



DDR Degauss, Destroy, Recycle Workstations



DDM
Degauss, Destroy, Mobility



DD
Degauss, Destroy



SSC-25SSD SPACESAVER

Specifications	EDC Enclosed Destruction Cart	RCC Data Eliminator Cart	DDR Degauss, Destroy, Recycle Workstations	DDM Degauss, Destroy, Mobility	DD Degauss, Destroy	SSC-25SSD SPACESAVER
Degausser Options	TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser	TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser HD-3XTL high-volume degausser HD-2XT high-speed degausser	TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser HD-3XTL high-volume degausser HD-2XT high-speed degausser	TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser HD-3XTL high-volume degausser HD-2XT high-speed degausser	TS-4XT 40,000 Gauss degausser TS-1XT NSA Listed degausser HD-3XTL high-volume degausser HD-2XT high-speed degausser	HD-2XTSS high-speed degausser (Same specifications as HD-2XT)
Destroyers Options	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer	PD-5 NSA Listed HDD destroyer SSD-1 SSD destroyer
Verification Options	IRONCLAD optional SCAN-1X standard	IRONCLAD optional SCAN-1X standard (opional with HD-2XT packages)	IRONCLAD optional SCAN-1X optional (opional with HD-2XT packages)	IRONCLAD optional SCAN-1X optional (opional with HD-2XT packages)	IRONCLAD optional SCAN-1X optional (opional with HD-2XT packages)	IRONCLAD optional SCAN-1X standard
Platform	CART-ICC Mobile Destruction Cart	CART-RCCR Data Eliminator Cart	SW-2 workstation table and bins	Transport Case	.	SSD-CADDY destruction accessory station
Features & Benefits	<ul style="list-style-type: none"> Take destruction to the media Maintains chain-of-custody Eliminates risk of physical data breach Removable doors Large wheels provide effortless maneuvering Superior turning capabilities Provides power for additional equipment 	<ul style="list-style-type: none"> Take destruction to the media Maintains chain-of-custody Eliminates risk of physical data breach Agile and safe mobile operations Superior turning capabilities Provides power for additional equipment Strong, lightweight aluminum construction 	<ul style="list-style-type: none"> Custom designed table Locking storage compartment Includes one large shatter resistant recycling bin Includes red media bin for media awaiting degaussing and yellow media bin for after degaussing 	<ul style="list-style-type: none"> Die-cut foam to protect equipment during transit High-quality ball bearings, smooth-rolling wheels Full-swivel, locking, and removable casters Recessed handles Recessed latches for secure transport Fits through standard doorways and into elevators 	<ul style="list-style-type: none"> Complete data erasure in seconds Physical destruction provides visual evidence media has been sanitized 	<ul style="list-style-type: none"> Regulatory compliance in a small footprint Exclusive vertical HD-2XTSS Includes patented SSD-1 solid-state destroyer SCAN-1X Media Destruction Report software and scanner
Power	CART-EDC: Shore power	CART-RCC: Shore power	SW-2 Table: N/A	Cases: N/A	See individual product descriptions	See individual product descriptions
Weight	CART-EDC: 490 lbs. (222.3 kg) fully equipped*	CART-RCC: 71 lbs. (32.2 kg)	SW-2 Table: 195 lbs. (88.45 kg)	Cases: weight varies depending on package	See individual product descriptions	See individual product descriptions
Size	CART-EDC: 42.7 x 30.4 x 36.4 (in.) 1085.8 x 772 X 924.4(mm) Height w/IRONCLAD option 53.8 in. (1365.3 mm)* Depth with handle 39.09 in. (992.9 mm)	CART-RCC: 42 x 24 x 43 (in.) / 106.68 x 60.96 x 109.22 (cm)	SW-2 Table: 36 x 50 x 28 in. 914.4 x 1270 x 711.2 mm.	Cases: weight varies depending on package	See individual product descriptions	See individual product descriptions
Warranty	CART-ICC: One-year parts and labor	CART-RCCR: One-year parts and labor	SW-2 table: One-year parts and labor	CASES: Ninety-day limited warranty standard	See individual product descriptions	See individual product descriptions

For components, please see individual product warranty descriptions
* Specifications may vary depending on part number ordered. Contact your account manager for specifications.