



MASTERS OF DESTRUCTION

HDD DISASSEMBLER

DiskMantler™
HDS-35SL



*5 Hard Drives
5 Minutes*



Through a process of shock, harmonics, and vibration, the DiskMantler™ efficiently disassembles decommissioned hard drives into their largest components--the case, cover, PC board, platters, voice coil, and rare-earth magnets.



This hands-free, automated disassembly process only takes 8 to 90 seconds per drive, depending on user's desired degree of component separation.



By separating the valuable internal components from its casing, the components are ready for responsible recycling. This process, significantly reduces e-waste minimizing adverse environmental effects, and replaces traditional shredding and melting methods.



Patent Pending

GarnerProducts.com

Tel: 916-784-0200 Fax: 916-784-1425

10620 Industrial Avenue, Suite 100, Roseville, CA 95678

1-800-624-1903

Prices and specifications subject to change without notice.

©2024 Garner Products, Inc. All rights reserved. 2024-25-03



Seamless Operation

Simply insert the HDD into the media slot. The internal automated system carries the HDD into the disassembly chamber, and then transfers the recyclable components down the exit slot.

Easy Maintenance

The sides of the unit are equipped with quick-disconnect latches and two handles for easy access to the removable debris tray and internal components.

Max Recycling Value

Valuable, intact components, including rare earth magnets and PC boards, are easily sorted for recycling or responsible disposal.

Compact size

A footprint of 23.5" x 14.8" x 44.6" (HxWxD) allows for seamless integration into existing environments.



Watch our [video](#) to see the DiskMantler in action.

GarnerProducts.com

Garner Products Inc.
10620 Industrial Avenue
Suite 100
Roseville, CA 95678 USA

1-800-624-1903

Tel: 916-784-0200 Fax: 916-784-1425
Prices and specifications subject to change without notice.
©2024 Garner Products, Inc. All rights reserved.



Controls and Indicators



1. Action button
2. Disassembly time dial
3. LCD display
4. Emergency stop
5. HEPA port
6. Light tower



1. Quick disconnect latches
2. Media entrance slot
3. Handles for removing side panel
4. Exit ramp



1. Air release valve
2. Air lubricator reservoir
3. Air pressure valve
4. Air supply port
5. Air pressure gauge

Regulatory Compliance

In addition to the recycling benefits, the DiskMantler will help you meet the most stringent government and industry standards requiring media data destruction prior to disposal, including:

- » **CCPA (California Consumer Privacy Act)**
- » **DoD (Department of Defense)**
- » **GDPR (General Data Protection Regulation)**
- » **GLBA (Gramm-Leach-Bliley Act)**
- » **HIPAA (Health Information Portability and Accountability Act)**
- » **IRS 1075**
- » **NIST SP 800-88r1**
- » **PCI DSS 3.2 (Payment Card Industry Data Security Standard)**
- » **PIPEDA (Personal Information Protection and Electronic Documents Act)**
- » **TAA compliant**

DiskMantler Specifications

Part Numbers	HDS-35SL: North America HDS-35SLA: LATAM HDS-35SLE: APAC, EMEA
Media	Standard 1" thick max 3.5" hard drives
Power	100~250VAC ±5%, 50/60 Hz
Power Consumption	305W max
Air Supply	15 CFM @ 120 psi minimum
Certifications	CE • TAA compliant
Temperature	41°F - 104°F (5°C - 40°C)
Humidity	10%H - 40%H (without condensation)
Weight	202 lbs. (92 kg.)
Size (HxWxD)	23.5 x 14.8 x 44.6 in. (597 x 376 x 1133 mm)
Warranty	HDS-35SL • HDS-35SLA • HDS-35SLE: One-year manufacturer's limited warranty standard.
Service Plans	Optional manufacturer services plans available.
Optional Accessories	Piston alignment tool Programming cable Pneumatic oil Service tools
Made in USA	By Garner Products, Inc.

Add Garner's exclusive DeMag™

Generating nearly 4 Tesla, the DeMag's magnetic fields effectively demagnetizes all magnets within the drive, including the disk platters. Used as the first step in sanitization and recycling, and then followed by the DiskMantler, the demagnetized hard drive enables the magnets to easily detach from the housing when being disassembled by the DiskMantler. This enhances magnet handling efficiency during the disassembly and recycling process by preventing the magnets from sticking to one another and other objects.

